

**0717** 

TYRI developed the 0717 with the latest in LED technology. Boasting special automotive style optics and up to 2,150 effective lumen's this LED can swivel 360° and 60° vertical adjustment for maximum mounting options.

The 0717 is highly adaptable and can be used across numerous applications worldwide, including agriculture.



#### **TECHNICAL DATA**

Housing Material: Cast Aluminium

**Mounting Options:** Hanging

Standing

Lens Material: Polycarbonate

Temperature range: -40 to +85 °C

Connector: Deutsch (DT04-2P)

built in

Weight: 800 g / 1,76 lb

**Light Patterns:** Short Range

Long Range

## **FEATURES**



Overheating Protection



Over-voltage Protection



Polarity Protection



CE - marked

# **TEST STANDARDS**



Salt Spray ASTM B117 48+100 h



Vibration 5-2000 Hz 3 Axis, 10 Grms



Shock Tested 50 G



IP69K


R10




EN55025 / CISPR 25 Class 5, ISO 7637-2, ISO 16750-2, ISO 10605, ISO 11452-2, ISO 11452-4



For further infomation visit www.tyrilights.com or contact your local sales team.









# 0717

LIGHT OUTPUT	VOLTAGE		AMP DRAW		POWER	COLOUR TEMPERATURE	EMC	ECE
Effective Lumen	Machine	Operating	12 V	24 V	Watts	К	EN55025 / CISPR25	ECE Rating
2,150 eLm Short Range	12 V	9-16 V	2,5 A	- A	30 W	5,700 K	5	R10
2,150 eLm Long Range	12 V	9-16 V	2,5 A	- A	30 W	5,700 K	5	R10

## **TYPICAL LIGHT PATTERNS**



**0717 Short Range** Medium, 31 - 45° 3.0 m / -15° Asymmetric



**0717 Long Range** Narrow, 0-30° 3.0 m / -15° Symmetric

