




1005A MARKER

The 1005A Marker LED is the smallest of the TYRI markers. It is available with flying leads and UL approval, ensuring it is a smart choice for your market needs.





Additional uses for this light is as a dome light or indicator and is available in amber and clear colour lens options.





TECHNICAL DATA

Housing Material:	PC
Mounting Options:	Flush
Lens Material:	Amber & Clear PC
Temperature range:	-40 to +75 °C
Connector:	Bare wires


FEATURES

-  Overheating Protection
-  Over-voltage Protection
-  Polarity Protection
-  UL Rated

TEST STANDARDS

-  IP69K
-  EN55025 / CISPR 25 Class 5
ISO 11452-2 / ISO 11452-4
ISO 16750-2 / ISO 10605
ISO 7637-2

For further information visit www.tyriLights.com or contact your local sales team.





1005A MARKER

LENS COLOUR	VOLTAGE		AMP DRAW		POWER	EMC	ECE
	Machine	Operating	12 V	24 V		EN55025 / CISPR25	ECE Rating
Amber	12 V	9-16 V	0,08 A	- A	1 W	5	-
Amber	24-48 V	18-60 V	- A	0,04 A	1 W	5	-
Clear	12 V	9-16 V	0,08 A	- A	1 W	5	-
Clear	24-48 V	18-60 V	- A	0,04 A	1 W	5	-

Product may not be available in all territories. Please check with your local TYRI office.

LED work lights are exposed to dirt, fertilizers, road salt, acids and more. For best performance and long lifetime, the lens and the cooling fins must be cleaned on a regular basis.