

D8 SWIVEL BLUEPOINT

D8 Swivel Bluepoint increases safety and minimises the risk of accidents around machinery. It allows safety to be visual instead of relying solely on sirens and alarms. The D8 Swivel Bluepoint projects a light beam as a concentrated, visible square on the floor in front or behind the machine.

This warning light is also available as a standard work light, allowing you to match your machine lighting for a unified design.



Note: the lens of the Bluepoint is clear, the blue light is emitted from LEDs

TECHNICAL DATA

Housing Material: Cast Aluminium

Mounting Options: Hanging

Standing

Side

Lens Material: Polycarbonate

Temperature range: $-40 \text{ to } +85 \text{ }^{\circ}\text{C}$

Connector: Deutch (DT04-2P)

built in.

Mating part: DT06-2S

Weight: 525 g/ 1,16 lb

Light Patterns: Spot

FEATURES



Overheating Protection



Over-voltage Protection



Polarity Protection



CE - marked

TEST STANDARDS



Salt Spray ASTM B117 48 h



Vibration 12-200 Hz 3 Axis, 14G



Shock Tested 50 G 10 ms





IP69K



EN55025 / CISPR 25 Class 3, ISO 7637-2, ISO 16750-2, ISO 10605, EN610000-4-2, EN610000-4-3, EN610000-4-4, EN610000-6-3

For further infomation visit www.tyrilights.com or contact your local sales team.







D8 SWIVEL BLUEPOINT

LIGHT OUTPUT	VOLTAGE		AMP DRAW		POWER	DOMINANT WAVELENGTH	EMC	ECE
Candela	Machine	Operating	12 V	24 V	Watts	nm	EN55025 / CISPR25	ECE Rating
20,000 cd	12-48 V	9-60 V	1,1 A	0,6 A	15 W	475 nm	3	-

IEC/SS-EN 62471 | RISK GROUP 2

CAUTION: Possibly hazardous optical radiation emitted from this product.

Do not stare at operating lamp. May be harmful to the eye.

It is important to remember, LED work lights are no more hazardous than other lighting technologies with the same correlated colour temperature (CCT).

TYRI complies with the IEC/SS-EN 62471 standard with the addition of the warning label on the product.